

5MP ColourHunter Fixed Bullet Analog Camera

UAC-B115-AF28(40)-W



Introduction

UAC-B115-AF28(40)-W is a 5MP ColourHunter fixed bullet analog camera with a high-performance 1/2.7-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference mega-pixel HD video transmission without time delay. The camera also supports audio input and synchronous transmission of audio and video.

Features


- 5MP high quality image
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables

Specifications

Model	UAC-B115-AF28-W		UAC-B115-AF40-W	
Sensor				
Pixel	5MP			
Size	1/2.7"			
Minimum illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)			
Lens				
Lens	2.8mm		4.0mm	
Lens mount	M12			
Angle of view	H: 110.0° V: 57.0° D: 130.0°		H: 90.0° V: 48.0° D: 109.1°	
Illuminator				
Illuminator	One white-light illuminator			
Illumination distance	20m			
Lifetime	≥60,000 hours			
Video				
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) 4MP: 2560(H)×1440(V) 1080P: 1920(H)×1080(V)			
Frame rate	TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC			
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s–1/50000s			
Image				
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR			
Day/Night	24/7 color images			
Digital noise reduction	2D			
White balance	Two modes: Auto (default), Manual			
WDR	DWDR			
Flip	Supports 180° horizontal flip, 180° vertical flip			
Defog	N/A			
Audio				
Microphone	Built-in Mic			
Camera audio	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps			
Interface				
Power	5.5mm power interface			
Video output	BNC, supports TVI/AHD/CVI/CVBS			
Operating environment				
Temperature	-30°C to 60°C(-22°F to 140°F)			
Humidity	≤95% (RH, non-condensing)			
Surge protection	4KV			

General	
Power	DC 12V(±25%), with reverse polarity protection, Max 2.3W
Mount	Surface mount (default), optional backbox, pole mount bracket
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Graphene+Plastic
Weight	150g (0.33lb)
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish
Certification	
EMC	CE-EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)

Dimensions



UAC-B115-AF28(40)-W

Accessories

TR-JB05-A-IN

Junction Box



TR-UC08-C

TR-UP06-B-IN

Pole Mount



PWR-DC1201A-UK

TR-UP06-C-IN

Pole Mount



PWR-DC1201A-US

TR-A01-IN

Waterproof Joint



PWR-DC1201A-EU

Corner Mount



Wall Plug-in UK Power Adapter



Wall Plug-in US Power Adapter



Wall Plug-in EU Power Adapter



Mount	
TR-UP06-B-IN	TR-JB05-A-IN+TR-UP06-C-IN
TR-JB05-A-IN+TR-UC08-C	

Zhejiang Uniview Technologies Co., Ltd.

Building No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, Zhejiang Province, China (310051)

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<https://www.uniview.com>

©2023 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.